

Stansolv 519



DESCRIPTION AND GENERAL PROPERTIES

- Material Nitrile
- Length (cm) 33
- Thickness (mm) 0.30
- Colour/Color Green
- Interior finish Chlorinated
- Exterior finish Chlorinated
- Size / EAN 7 8 9 10
- Packaging 1 pair/bag - 12 pairs/bag - 72 pairs/carton
- Complementary information Guaranteed without silicone
Class 100 (ISO 4) Compatible



PERFORMANCE RESULTS

Certification category 3

CE 0334




3001

Legends



MECHANICAL HAZARDS
EN 388

PERFORMANCE LEVELS



LOW CHEMICAL PROTECTION
EN 374



MICRO-ORGANISMS
EN 374




RADIOACTIVE CONTAMINATION
EN 421



HEAT AND FIRE
EN 407

PERFORMANCE LEVELS




SPECIFIC CHEMICAL PROTECTION
EN 374

Letter Code	Chemical product
A	Methanol
B	Acetone
C	Acetonitrile
D	Dichloromethane
E	Carbon Disulfide
F	Toluene
G	Diethylamine
H	Tetrahydrofurane
I	Ethyl acetate
J	n-Heptane
K	Sodium hydroxide 40%
L	Sulphuric acid 96%



COLD HAZARDS
EN 511

PERFORMANCE LEVELS



For more details: www.mapa-pro.com

DESCRIPTION AND GENERAL PROPERTIES

- Manufacturing process guarantees a very low level of contaminants: rates of particles, non-volatile residue, extractables => compatible with ISO 5 class (Class M3.5 for International system)
- Optimal dexterity without compromising chemical resistance
- Better resistance than natural latex gloves against organic solvents
- Recommended for people sensitive to the proteins in natural latex

MAIN FIELDS OF USE**Mapa Advantech**

- Controlled Environment: Product and user protection

INSTRUCTIONS FOR USE**Instructions for use**

- Persons sensitized to dithiocarbamates and thiazoles should not use these gloves.
- Unpack and put on the gloves according to the gowning procedure in the workplace. Place the fingers into the glove. Gently pull the glove over the hand and make final adjustments only when both hands are gloved.
- Put the gloves on dry, clean hands.
- It is recommended to check that the gloves are suitable for the intended use, because the conditions of use at workplace may differ from the «CE»-type tests.
- Do not use the gloves in contact with a chemical for a duration in excess of the measured breakthrough time. Refer to the website www.mapa-pro.com or contact the Technical Customer Service - MAPA PROFESSIONNEL (stc.mapaspontex@mapaspontex.fr) in order to know this breakthrough time. Use 2 pairs alternatively when in long duration contact with a solvent.
- Turn the cuff end down in order to prevent a hazardous chemical from dripping onto the arm.
- Take off the gloves without touching the external surface : pull off a first glove and hold it with the gloved hand. Fold back the cuff edge of the second glove over both gloves and discard in appropriate refuse container.

Storage conditions

Store the gloves in their packaging protected from light, humidity and heat.

LEGISLATION

This product is not classified hazardous according to the regulation (EC) n°1272/2008 of the European Parliament and of the Council. This product does not contain more than 0.1 % of substance of very high concern (SVHC) or any substance included in the annex XVII of the regulation n° 1907/2006 of the European Parliament and of the Council (REACH).

- CE-Type Examination Certificate

0075/014/162/09/09/0407

- Issued by the notified body nr

0075

C.T.C - 4, rue Hermann Frenkel -69367 Lyon cedex 07 - France

- Quality assurance certificat

0334 Asqual 14 rue des Reculettes -F-75013 PARIS